REC LITE SPARK®



Capacity	SPARK® 2up	
Rider capacity		
Weight capacity	160 kg	
Fuel capacity	30 L	
Storage capacity - Glove Box	0.1.6 L	
Storage capacity - Front Bin	27 L (900 ACE™ Accessory)	
Dimensions		
Length	279 cm	
Width	118 cm	
Height	41"/ 104 cm	
Hull		
Туре	SPARK® Hull	
Material	Polytec [™] - Lightweight and Scratch resistant	

Handlegrip with Palm Rests

Tow Hook

Rotax® Engine	900 ACE™	900 HO ACE™
Model	2-up	2-up
Intake system	Naturally aspirated	
Displacement	899 cc	
Cooling	Closed-Loop Cooling system (CLCS)	
Reverse system	Manual Reverse Kit (Accessory)	Electronic iBR®*
Fuel type	95 octane	
Throttle System	iTC™ (Intelligent Throttle Control) system	
Exhaust System	D-Sea-Bel™ system	
Gauge	900 ACE™	900 HO ACE™
Type of Gauge	Compact	
Main Functions	Speedometer RPM Vehicle Hour Display	Speedometer RPM Vehicle Hour Display Sport Mode
Weight	900 ACE™	900 HO ACE™
Dry weight	184 kg	190 kg
Warranty BRP limited warranty covers the	watercraft for two years.	


Slim Seat

Seat Strap

Wetgrip Footboard



Feature Highlights



High-quality, waterproof 50-watt Bluetooth $\!\!\!^{\ddagger}$ portable sound system.



Additional storage space to bring more gear on board.



Innovative material that reduces weight while optimizing performance and efficiency. The color-in molding is more scratch-resistant than fiberglass.



Designed to improve freedom of movement while riding.



Two fuel efficient, compact and lightweight Rotax® engine options.



Makes boarding from the water easier and quicker.

